



Dna elipsoidalne wg PN-64/M-35411

Średnica zewnętrzna	Wymiar	Grubość ścianki s mm									
		3	4	5	6	7	8	9	10	12	
		Wymiar hc mm									
		20			25				40		
Dz	hz	masa kg									
33,7	8,5	0,07	-	-	-	-	-	-	-	-	-
38,0	9,5	0,08	-	-	-	-	-	-	-	-	-
44,5	11	0,11	-	-	-	-	-	-	-	-	-
57,0	14	-	0,25	-	-	-	-	-	-	-	-
60,3	15	-	0,27	-	-	-	-	-	-	-	-
76,1	19	-	0,32	-	-	-	-	-	-	-	-
88,9	22	-	0,41	-	-	-	-	-	-	-	-
108,0	27	-	0,70	-	-	-	-	-	-	-	-
114,0	28	-	0,72	-	-	-	-	-	-	-	-
133,0	33	-	0,82	-	-	-	-	-	-	-	-
159,0	40	-	1,20	1,50	-	-	-	-	-	-	-
168,0	42	-	1,30	1,60	-	-	-	-	-	-	-
194,0	49	-	1,80	2,20	2,80	-	-	-	-	-	-
219,0	55	-	2,10	2,50	3,20	3,50	-	-	-	-	-
273,0	69	-	2,70	3,80	4,70	5,50	6,30	-	-	-	-
324,0	81	-	4,10	5,10	6,40	7,40	8,50	10,60	-	-	-
356,0	89	-	4,90	6,10	7,70	8,70	10,00	12,50	-	-	-
406,0	102	-	6,50	7,80	9,70	11,40	12,80	15,80	17,70	-	-
457,0	115	-	7,90	9,90	12,20	14,30	16,30	19,80	22,00	26,30	-
508,0	127	-	9,70	12,00	14,90	17,30	19,80	24,00	26,60	33,10	-